

## DEPENDENT RESURVEY, SEVENTH STANDARD PARALLEL NORTH, R. 37 E.

CHAINS	RETRACEMENT AND PARTIAL DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL NORTH, THROUGH R. 37 E., MDM., NEVADA
	<p>Reestablishment of the survey executed by W. Epler, U. S. Deputy Surveyor, in 1867.</p> <hr/> <p>Beginning at the standard corner of T. 36 N., Rs. 37 and 38 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of T. 36 N., R. 38 E., executed under this same group.</p> <p>S. 89° 51' W., along the S. bdy. of sec. 36.</p> <p>Over gently rolling land, through medium undergrowth.</p>
8.12	The closing cor. of T. 35 N., Rs. 37 and 38 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 35 N., R. 38 E., executed under this same group.
37.50	Trail road, winding ENE. and W.
40.095	Point for the standard ¼ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.
	Corner not remonumented.
45.20	Old Humboldt Canal, bears NNE. and SSW.
48.90	Trail road, bears SSE. and NNW.
58.40	Telephone line, bears N. and S.
59.10	U. S. Highway Nos. 40 and 95, bear N. 56° E. and S. 56° W.
61.60	Power line, in fence, bears irregularly N. and S.
66.50	Slough, drains S.
71.80	Same slough, drains NW.
80.19	Point for the standard cor. of secs. 35 and 36, at intersection with an old property line fence bearing N. and S. This fence is accepted as the best available evidence of the longitudinal position of the original corner. There is no remaining evidence of the original corner.
	Corner not remonumented.
	Land, gently rolling. Soil, sandy and sandy clay. Undergrowth, sagebrush, native grasses and shadscale.