

DEPENDENT RESURVEY OF THE W. BDY., T. 36 N., R. 37 E.

CHAINS

T36N
R36E R37E
S 12 | S 7

1965

reset the wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. 0° 04' E., beginning new measurement.

Over rolling land; asc. 90 ft. over S. slope.

- 16.50 Ridge, bears SW. and E.; desc. 30 ft. over N. slope.
- 22.50 Trail road, bears irregularly ESE. and WNW.; asc. 100 ft. over SW. slope to cor.
- 37.00 Trail road, bears NE. and SW.
- 37.30 Wash, 20 lks. wide, 1 ft. deep, drains SW.
- 40.42 The cor. of secs. 1, 6, 7 and 12, monumented with a trap-stone, 6x8x12 ins., plainly mkd. 5 notches on the S. face and 1 notch on the N. face and firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to cap, with brass cap mkd.

T36N
R36E R37E
S 1 | S 6
S 12 | S 7

1965

bury the original corner stone alongside the iron post.

Land, rolling.
Soil, sandy clay.
Undergrowth, sagebrush.

N. 0° 02' E., bet. secs. 1 and 6.

Over rolling land, through medium undergrowth.

- 1.00 Spur, slopes WSW.
- 5.60 Trail road, bears NE. and SW.; asc. 180 ft. over S. slope.
- 20.30 Remains of old mill site.
- 24.00 Spur, slopes E.; desc. 210 ft. over N. slope to cor.
- 24.40 NW. corner of mine shaft, bears W. 17 lks. dist.