

DEPENDENT RESURVEY, T. 36 N., R. 37 E.

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 36 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA.

Reestablishment of a portion of the Survey Executed by A. J. Hatch, U. S. Deputy Surveyor, in 1868, and the Survey Executed by H. B. Maxson, U. S. Deputy Surveyor, in 1888.

The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, determined latitudinally at proportionate distance and longitudinally in line with old fence to the S.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins diam., 26 ins. in the ground, with brass cap mkd.

T36N R37E

S 26 | $\frac{1}{4}$ S 25

1965

set a wooden post, 4x6x84 ins. long, 42 ins. in the ground, W. of cor.

From this cor., the point for the standard cor. of secs. 35 and 36, T. 36 N., R. 37 E., not remonumented, bears S. $0^{\circ} 02' W.$, 120.63 chs. dist.

N. $0^{\circ} 56' E.$, bet. secs. 25 and 26.

Over general SE. slope, through medium undergrowth; asc. 130 ft. to cor.

- 5.70 Trail road, bears E. and W.
- 6.30 South edge of gravel pit, bears E. and W.
- 11.30 North edge of gravel pit, bears E. and W.
- 39.90 Trail road, winding E. and W.
- 40.21 The cor. of secs. 23, 24, 25 and 26, monumented with a mound of stone buried in the sod, no mkd. stone found.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins diam., 24 ins. in the ground, with brass cap mkd.

T36N R37E

S 23 | S 24
S 26 | S 25

1965

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.