

## DEPENDENT RESURVEY, S. BDY., T. 34 N., R. 38 E.

## CHAINS

locally recognized as the true corner point and is accepted as the best remaining evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T34N R38E
S32
—
¼ S 5
T33N

1965

reset the iron pipe alongside the iron post and raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.

S. 89° 59' W., beginning new measurement.

Desc. 60 ft. over a gentle W. slope to sec. cor.

- 6.90 Trail road, bears NNW. and SSE.
- 22.50 Bladed dirt road, bears NE. and SW.
- 40.19 The cor. of secs. 5, 6, 31, and 32, monumented with an iron pipe, 1 in. diam., exposed 6 ins. above ground, locally recognized as the true corner point and is accepted as the best remaining evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2 ½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T34N R38E
S31   S32
—   —
S 6   S 5
T33N

1965

reset the iron pipe alongside the iron post and raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.

Land, gentle W. slope

Soil, sandy clay.

Undergrowth, sagebrush, June grass and budsage.

Timber, none.

S. 89° 57' W., bet. secs. 6 and 31.

Over gently rolling land, through medium undergrowth; desc. 50 ft. over gentle W. slope to ¼ sec. cor.

- 5.70 Trail road, bears NNE. and SSW.