

DEPENDENT RESURVEY OF A PORTION OF THE W. BDY.,
T. 35 N., R 38 E.

CHAINS

N. 0° 10' W., beginning new measurement.

Over nearly level land, along bladed strip.

40.02

The cor. of secs. 1, 6, 7 and 12, monumented with a wooden post, 2 x 3 x 12 ins. long, firmly set alongside a railroad tie, 8 ins. x 7 ins. x 6 ft. long.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35N	
R37E	R38E
S 1	S 6
S 12	S 7

1965

bury the wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, nearly level.
Soil, sandy clay.
Undergrowth, sagebrush.

N. 0° 16' W., bet. secs. 1 and 6.

Over nearly level land, through medium undergrowth, along bladed strip.

14.20

REA power line, bears N. 62½° E. and S. 62½° W.

24.60

REA power line, bears N. 28½° E. and S. 28½° W.

25.50

Grass Valley Road, bears N 28½° E. and S. 28½° W.

36.20

Fence, curving NE. and SW.

39.70

Telephone line, curving NE. and SW.

39.99

The ¼ sec. cor. of secs. 1 and 6, monumented with a steel pipe, ½ in. diam., set 15 ins. in the ground. This steel pipe is locally accepted as the corner and is the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35N	
R37E	R38E
S 1	S 6

1965