DEPENDENT RESURVEY OF THE W. BDY., T. 35 N., R. 39 E.

CHAINS	
	N. 0° 04' W., beginning new measurement.
	Over mountainous land; asc. 120 ft. over SW. slope.
14.10	Ridge, bears E. and W.; desc. 150 ft. along W. slope.
20.10	Trail road, bears ENE. and WSW.; desc. 270 ft. along W. slope to cor.
38.17	The closing cor. of secs. 1 and 12, T. 35 N., R. 38 E., hereinafter described.
40.36	The cor. of secs. 6 and 7, monumented with a granite stone, 6 x 8 x 16 ins., firmly set in a mound of stone and plainly mkd. 5 notches on the S. face and 1 notch on the N. face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

<div align="center">

T35N

R38E R39E

S 1 | S 6
| S 7

1965

</div>

CHAINS	
	bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.
	Land, mountainous.
	Soil, sandy loam and rocky.
	Undergrowth, sagebrush
	Timber, scattered juniper, willows and cottonwood trees along canyons.
	N. 0° 05' W., along the W. bdy. of sec. 6.
	Over mountainous land, through medium undergrowth; desc. 80 ft. along W. slope.
2.10	Head of ravine, drains WNW.
10.30	Head of ravine, drains W.; asc. 50 ft. over S. slope.
16.80	Spur, slopes W.; desc. 380 ft. along a broken NW. slope.
38.33	The ¼ sec. cor. of secs. 1, T. 35 N., R. 38 E., hereinafter described.
40.31	The ¼ sec. cor. of sec. 6, monumented with a basalt stone, 4 x 8 x 14 ins., firmly set in a mound of stone and plainly mkd. ¼ on the W. face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.