

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 38 E.

CHAINS		
	Over mountainous land, through medium undergrowth; desc. 520 ft. over N. slope.	
30.70	Ravine, drains WNW.; asc. 140 ft. over S. slope.	
39.50	Spur, slopes W.; desc. 10 ft. over N. slope.	
40.43	The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented with a granite stone, 6 x 8 x 12 ins., buried in the sod and plainly mkd. $\frac{1}{4}$ on the W. face and a mound of stone to the W. of cor.	
	At the corner point	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone to cap, $3\frac{1}{2}$ ft. base, with brass cap mkd.	
	T35N R38E $\frac{1}{4}$ S 2 S 1 1965	
	bury the original corner stone alongside the iron post.	
	—————	
	NORTH, beginning new measurement.	
	Over mountainous land; desc. 460 ft. over NW. slope.	
38.90	Ravine, drains WNW.; asc. 70 ft. over S. slope.	
45.19	Intersect the Seventh Standard Parallel North.	
	The closing cor. of secs. 1 and 2, monumented with a basalt stone, 4 x 6 x 12 ins., firmly set in a mound of stone and dimly mkd. 1 notch on the E. face and 5 notches on the W. face.	
	At the corner point	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock and in a mound of stone to cap, $3\frac{1}{2}$ ft. base, with brass cap mkd.	
	T36N R38E S 35 S 2 S 1 CC T35N 1965.	
	bury the original corner stone alongside the iron post.	
	From this corner, the standard cor. of secs. 35 and 36, T. 36 N., R. 38 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of T. 36 N., R. 38 E., executed concurrently under this same group, bears EAST, 12.42 chs. dist.	