

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 35 N., R. 38 E.

CHAINS													
3.00	Fence cor.; fences bear S. and WNW.												
3.80	Ravine, drains WNW.												
5.00	Trail road, bears ESE. and WNW.; asc. 70 ft. over S. slope.												
19.60	Ravine, drains NW.												
29.00	Ravine, drains W.												
32.00	Ridge, bears E. and W.; desc. 50 ft. over N. slope.												
37.50	Ravine, drains NW.												
42.48	Intersect the Seventh Standard Parallel North.												
	Point for the closing corner of secs. 2 and 3.												
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T36N</td><td>R38E</td></tr> <tr><td>S</td><td>34</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2" style="text-align: center;">CC</td></tr> <tr><td colspan="2" style="text-align: center;">T35N</td></tr> <tr><td colspan="2" style="text-align: center;">1965</td></tr> </table>	T36N	R38E	S	34	S 3	S 2	CC		T35N		1965	
T36N	R38E												
S	34												
S 3	S 2												
CC													
T35N													
1965													
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.												
	From the point of intersection, the original closing cor. monumented with a granite stone, 8 x 10 x 16 ins., plainly mkd. 2 notches on the E. face, CC on the S. face and 4 notches on the W. face and in a collar of stone, bears N. 0° 19' W., 0.61 chs. dist. I marked the corner stone with the letters AM and rehabilitated the collar of stone; corner falls at corner of fences bearing E., SSE. and W.												
	From the same point of intersection, the standard cor. of secs. 34 and 35, T. 36 N., R. 38 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of T. 36 N., R. 38 E. executed concurrently under the same group, bears S. 89° 59' E., 3.63 chs. dist.												
	From the same point of intersection, the standard ¼ sec. cor. of sec. 34, T. 36 N., R. 38 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of T. 36 N., R. 38 E. executed concurrently under this same group, bears N. 89° 59' W., 36.45 chs. dist.												
	Land, rolling. Soil, sandy loam and rocky. Undergrowth, sagebrush.												
	Point for the ¼ sec. cor. on the N. bdy. of sec. 2 on the Seventh Standard Parallel North and at proportionate distance in longitude on the N. bdy. of sec. 2.												