

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 38 E.

CHAINS	
	Desc. 130 ft. over W. slope.
40.11	The cor. of secs. 3, 4, 9 and 10.
	Land, rolling.
	Soil, sandy loam.
	Undergrowth, sagebrush.
	N. 9° 04' W., bet. secs. 3 and 4.
	Over rolling land, through medium undergrowth; asc. 50 ft. over S. slope.
5.30	Top of ascent, bears W.; desc. 120 ft. over NW. slope.
25.50	Wash, 20 lks. wide, 5 ft. deep, drains W.; asc. 60 ft. over SW. slope.
39.22	The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, monumented with a granite stone, 4 x 6 x 10 ins., dimly mkd. $\frac{1}{4}$ on the W. face and buried in the sod.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T35N R38E
	S 4 $\frac{1}{4}$ S 3
	1965
	bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 0° 29' E., beginning new measurement.
	Over rolling land; desc. 70 ft. over N. slope.
19.20	Water Canyon, 30 lks. wide, 3 ft. deep, course W.
28.30	Trail road, bears ESE. and WNW.; desc. 30 ft. over N. slope to cor.
36.50	Gravel road, bears ESE. and WNW.
42.74	Intersect the Seventh Standard Parallel North.
	Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.