

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 38 E.

CHAINS

T35N R38E

S 5 | ^{1/4}S 4

1965

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Desc. 40 ft. over rolling N. slope to cor.

82.40 Fence, bears N. 87° 41' E. and S. 87° 41' W.

82.75 Intersect the Seventh Standard Parallel North.

Point for the closing cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T36N R38E

S 32
S 5 | S 4

CC
T35N

1965

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the standard cor. of secs. 32 and 33, T. 36 N., R. 38 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of T. 36 N., R. 38 E., bears N. 89° 51' E., 8.84 chs. dist.

From this same corner, the standard ¼ sec. cor. of sec. 32, T. 36 N., R. 38 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of T. 36 N., R. 38 E., executed concurrently under this same group, bears S. 89° 51' W., 31.255 chs. dist.

Land, rolling.
Soil, sandy loam.
Undergrowth, sagebrush.

Point for the ¼ sec. cor. on the N. bdy. of sec. 4 on the Seventh Standard Parallel North and at midpoint in longitude on the N. bdy. of sec. 4.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T36N R38E

¼ S 4
T35N

1965