

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 35 N., R. 38 E.

CHAINS

T35N R38E

$\frac{1}{2}$   
 S 6 | S 5

1965

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Asc. 10 ft. over S. slope.

42.90 Top of ascent, bears E. and W.; desc. 30 ft. over N. slope.

52.00 Trail road, bears E. and W.; asc. 10 ft. over S. slope.

71.20 Powerline and trail road, bears NE. and SW.

82.92 Intersect the Seventh Standard Parallel North.

Point for the closing cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T36N R38E

S 31  
 S 6 | S 5

CC

T35N

1965

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the standard cor. of secs. 31 and 32, T. 36 N., R. 38 E., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of T. 36 N., R. 38 E., executed concurrently under this same group, bears N.  $89^{\circ} 51' E.$ , 8.60 chs. dist.

From this same corner, the standard  $\frac{1}{4}$  sec. cor. of sec. 31, T. 36 N., R. 38 E., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of T. 36 N., R. 38 E., executed concurrently under this same group, bears S.  $89^{\circ} 51' W.$ , 31.495 chs. dist.

Land, gently rolling.  
Soil, sandy loam.  
Undergrowth, sagebrush.

---

Point for the  $\frac{1}{4}$  sec. cor. on the N. bdy. of sec. 5 on the Seventh Standard Parallel North and at midpoint in longitude on the N. bdy. of sec. 5.