

DEPENDENT RESURVEY, SEVENTH STANDARD PARALLEL NORTH, R. 38 E.

CHAINS

40.095 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

SC
T36N R38E
 $\frac{1}{4}$ S 32

1965

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

From this corner, fence corner bears S. $31^{\circ} 26'$ W., 1.70 chs. dist., from which fence bears N. $87^{\circ} 41'$ E. and S. $32^{\circ} 45'$ W.

Desc. 80 ft. over rolling W. slope.

8.72 The $\frac{1}{4}$ sec. cor. on the N. bdy. of sec. 5, T. 35 N., R. 38 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 35 N., R. 38 E.

Desc. 100 ft. over rolling W. slope.

77.70 Power line, bears N. $43^{\circ} 06'$ E. and S. $43^{\circ} 06'$ W.

80.19 Point for the standard cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

SC
T36N R38E
S 31 | S 32

1965

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Land, rolling.

Soil, sandy.

Undergrowth, sagebrush.

S. $89^{\circ} 51'$ W., along the S. bdy. of sec. 31.

Over gently rolling land; through medium undergrowth.

3.00 Graded gravel road to city dump, bears S. 18° E. and N. 18° W.

8.60 The closing cor. of secs. 5 and 6, T. 35 N., R. 38 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 35 N., R. 38 E.