

## EIGHTH STANDARD PARALLEL NORTH, R. 33 E.

CHAINS	DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH, THROUGH R. 33 E., MDM., NEVADA										
	<p>Reestablishment of the Survey Executed by Hatch and Eaton, Deputy Surveyors, in 1873.</p> <hr/> <p>Beginning at the standard corner of T. 41 N., Rs. 33 and 34 E., monumented with a wooden post, 2x2x30 ins. long, with steel fence post alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> SC  T41N  R33E R34E  <u>S 36   S 31</u> </div> <p style="text-align: center;">1965</p> <p>reset the original wooden post and steel fence post alongside iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>N. 89° 45' W., along the S. bdy. of sec. 36.</p> <p>Over nearly level land, through medium undergrowth.</p> <tr> <td>26.40</td><td>REA powerline, bears N. 74° 10' E. and S. 74° 10' W.</td></tr> <tr> <td>33.13</td><td>The ¼ sec. cor. of sec. 1, T. 40 N., R. 33 E., herein- after described.</td></tr> <tr> <td>40.11</td><td> <p>Point for the standard ¼ sec. cor. of sec. 36, at pro- portionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> SC  T41N R33E  <u>¼ S 36</u> </div> <p style="text-align: center;">1965</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <tr> <td>73.16</td><td>The closing cor. of secs. 1 and 2, T. 40 N., R. 33 E., hereinafter described.</td></tr> <tr> <td>80.22</td><td> <p>The standard cor. of secs. 35 and 36, monumented with a wooden post, 2x2x30 ins. long, with steel fence post alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.</p> </td></tr> </td></tr>	26.40	REA powerline, bears N. 74° 10' E. and S. 74° 10' W.	33.13	The ¼ sec. cor. of sec. 1, T. 40 N., R. 33 E., herein- after described.	40.11	<p>Point for the standard ¼ sec. cor. of sec. 36, at pro- portionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> SC  T41N R33E  <u>¼ S 36</u> </div> <p style="text-align: center;">1965</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <tr> <td>73.16</td><td>The closing cor. of secs. 1 and 2, T. 40 N., R. 33 E., hereinafter described.</td></tr> <tr> <td>80.22</td><td> <p>The standard cor. of secs. 35 and 36, monumented with a wooden post, 2x2x30 ins. long, with steel fence post alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.</p> </td></tr>	73.16	The closing cor. of secs. 1 and 2, T. 40 N., R. 33 E., hereinafter described.	80.22	<p>The standard cor. of secs. 35 and 36, monumented with a wooden post, 2x2x30 ins. long, with steel fence post alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.</p>
26.40	REA powerline, bears N. 74° 10' E. and S. 74° 10' W.										
33.13	The ¼ sec. cor. of sec. 1, T. 40 N., R. 33 E., herein- after described.										
40.11	<p>Point for the standard ¼ sec. cor. of sec. 36, at pro- portionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> SC  T41N R33E  <u>¼ S 36</u> </div> <p style="text-align: center;">1965</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <tr> <td>73.16</td><td>The closing cor. of secs. 1 and 2, T. 40 N., R. 33 E., hereinafter described.</td></tr> <tr> <td>80.22</td><td> <p>The standard cor. of secs. 35 and 36, monumented with a wooden post, 2x2x30 ins. long, with steel fence post alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.</p> </td></tr>	73.16	The closing cor. of secs. 1 and 2, T. 40 N., R. 33 E., hereinafter described.	80.22	<p>The standard cor. of secs. 35 and 36, monumented with a wooden post, 2x2x30 ins. long, with steel fence post alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.</p>						
73.16	The closing cor. of secs. 1 and 2, T. 40 N., R. 33 E., hereinafter described.										
80.22	<p>The standard cor. of secs. 35 and 36, monumented with a wooden post, 2x2x30 ins. long, with steel fence post alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.</p>										