

EIGHTH STANDARD PARALLEL NORTH, R. 33 E.

CHAINS	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock and in a mound of stone, 3½ ft. base to cap, with brass cap mkd.</p> <p style="text-align: center;">T41N R33E A P <u>S 31</u></p> <p style="text-align: center;">1965</p> <p>bury the original corner stone alongside the iron post and reset steel fence post alongside.</p> <p>Land, rolling to broken. Soil, sandy and shalerock. Undergrowth, sagebrush and shadscale.</p>
14.20	Wash, 30 lks. wide, 3 ft. deep, drains S.
18.30	Wash, 40 lks. wide, 4 ft. deep, drains SE.; asc. 200 ft. over a NE. slope.
40.98	<p>Point for the standard ¼ sec. cor. of sec. 31, at 40.00 chs. in departure from the standard cor. of secs. 31 and 32.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 41N R33E <u>¼ S 31</u></p> <p style="text-align: center;">1965</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
41.59	The ¼ sec. cor. of sec. 6, T. 40 N., R. 33 E., hereinafter described.
56.17	<p>Point for the original standard ¼ sec. cor. of sec. 31, based on the record bearing and distance, of the resurvey of Winfred A. Pray, in 1912, from the standard cor. of T. 40 N., Rs. 32 and 33 E.; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R33E A P <u>S 31</u></p> <p style="text-align: center;">1965</p>