

DEPENDENT RESURVEY OF T. 40 N., R. 33 E.

CHAINS	
	N. 0° 20' E., bet. secs. 1 and 2.
	Over nearly level land, through medium undergrowth.
41.17	Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T40N R33E $\frac{1}{4}$ S 2 S 1 1965</p>
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
69.10	REA. powerline, bears N. 74° 10' E., and S. 74° 10' W.
81.93	The closing cor. of secs. 1 and 2, monumented with a wooden post, 2x2x30 ins. long, with steel fence post set alongside.
	This corner now becomes an amended monument and the wooden post is scribed AM and buried alongside the steel fence post.
82.54	Intersect the Eighth Standard Parallel North.
	Point for the closing cor. of secs. 1 and 2.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T41N R33E <u>S 36</u> S 2 S 1 CC T40N R33E 1965</p>
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From the point of intersection, the standard cor. of secs. 35 and 36, T. 41 N., R. 33 E., bears N. 89° 45' W., 7.06 chs. dist.
	Land, nearly level. Soil, sandy loam and alkali. Undergrowth, chadscale and greasewood.
	The point for the N. ¼ sec. cor. of sec. 1 is on the Eighth Standard Parallel North and at midpoint on the N. bdy. of sec. 1.