

DEPENDENT RESURVEY OF T. 40 N., R. 33 E.

CHAINS	
	Descend 10 ft. over a N. slope.
42.70	Wash, 40 lks. wide, 3 ft. deep, drains E.; asc. 20 ft. over a S. slope.
45.00	Low ridge, bears E. and W.; desc. 50 ft. over N. slope.
48.30	Fence, bears ENE. and WSW., 80 lks. dist., thence WNW.; asc. 410 ft. over a SE. slope.
64.80	Spur, slopes NE.; desc. 160 ft. over a N. slope.
71.98	Intersect the Eighth Standard Parallel North.
	Point for the closing cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 3½ ft. base to cap, with brass cap mkd.
	<div>T41N R33E</div> <div>S 32</div> <div>S 6   S 5</div> <div>CC</div> <div>T40N R33E</div>
	1965
	From the point of intersection, the standard cor. of secs. 31 and 32, T. 41 N., R. 33 E., bears N. 89° 45' W., 4.86 chs. dist.
	Land, rolling.
	Soil, sandy and shale rock.
	Undergrowth, shadscale and sagebrush.
	The point for the N. ¼ sec. cor. of sec. 5 is on the Eighth Standard Parallel North and at midpoint on the N. bdy. of sec. 5.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div>T41N R33E</div> <div>¼ S 5</div> <div>T40N</div>
	1965
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From this cor., the standard ¼ sec. cor. of sec. 32, T. 41 N., R. 33 E., bears N. 89° 45' W., 5.34 chs. dist.