

DEPENDENT RESURVEY, E. BDY., T. 42 N., R. 34 E.

CHAINS		
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T42N R34E R35E S 1 S 7 S 12 </p> <p style="text-align: center;">1965</p> <p>bury the original cornerstone alongside the iron post and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>Land, nearly level. Soil, sandy loam. Undergrowth, greasewood and shadscale.</p>	
	<p>N. 0° 27' E., along the E. bdy. of sec. 1.</p> <p>Over nearly level land, through medium undergrowth.</p>	
36.99	<p>The closing cor. of secs. 6 and 7, T. 42 N., R. 35 E., hereinafter described.</p>	
39.99	<p>The ¼ sec. cor. of sec. 1, monumented with a stone, 20x15x6 ins., firmly set and plainly mkd. ¼ on the W. face.</p>	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T42N R34E R35E ½ S 1 </p> <p style="text-align: center;">1965</p> <p>bury the original cornerstone alongside the iron post and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/>	
	<p>N. 0° 32' E., beginning new measurement.</p>	
37.00	<p>The ¼ sec. cor. of sec. 6, T. 42 N., R. 35 E., hereinafter described.</p>	
40.26	<p>The cor. of Tps. 42 and 43 N., R. 34 E., monumented with a stone, 16x8x8 ins., firmly set and plainly mkd. 6 notches on the N. and W. faces.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	