## SURVEY OF THE SUBDIVISION, T. 42 N., R. 35 E.

	CONVERT OF THE SUBDIVISION, 1. 42 N., R. 33 E.
CHAINS	S. 0° 02' E., bet. secs. 33 and 34.
	Over gently rolling land, through medium undergrowth.
2.30	Trail road, bears irregularly E. and W.
40.00	Point for the 1/2 sec. cor. of secs. 33 and 34.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T42N R35E
	s 33 s 34
	1965
	raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.
55.00	Desc. 80 ft. over a SE. slope.
80.00	Point for the/1/16 sec. cor. of sec. 33.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	1/16 S 33 80
	1965
	raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.
80.46	Power line, bears N. 67° 12' W. and S. 67° 12' E.
85.20	Intersect the N. bdy. of T. 41 N., R. 35 E.
	Point for the closing cor. of secs. 33 and 34.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T42N R35E CC
	S 33   S 34 S 3 T41N
	1965
	raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.
	from this corner
	The cor. of secs. 3 and 4, T. 41 N., R. 35 E., bears S. 88° 08' W., 3.65 chs. dist.
	The ½ sec. cor. of sec. 3, T. 41 N., R. 35 E., bears N. 88° 08' E., 36.17 chs. dist.
	Land, gently rolling. Soil, sandy.