

SURVEY OF THE SUBDIVISION, T. 42 N., R. 35 E.

CHAINS	
	WEST, bet. secs. 18 and 19.
	Over gently rolling land, through medium undergrowth; desc. 50 ft. over a gradual W. slope.
12.40	Desert road, bears NNW. and S.; desc. 30 ft. over a gradual W. slope.
25.00	Bottom of descent; continue over nearly level land.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\begin{array}{cc} R42N & R35E \\ \frac{1}{4}S & 18 \\ \frac{1}{4}S & 19 \end{array}$
	1965
	raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.
80.00	Point for the $\frac{80}{1/16}$ sec. cor. of secs. 18 and 19.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$1/16 \frac{S \ 18}{S \ 19} \ 80$
	1965
	raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.
89.59	Intersect the E. bdy. of T. 42 N., R. 34 E.
	Point for the closing cor. of secs. 18 and 19.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\begin{array}{ccc} T42N & & \\ R34E & R35E & \\ S \ 13 & \frac{S \ 18}{S \ 19} & CC \end{array}$
	1965
	raise a mound of stone, 2 ft. base, 2 ft. high, E. of cor.
	from this corner
	The $\frac{1}{4}$ sec. cor. of sec. 13, T. 42 N., R. 34 E., bears N. $0^{\circ} 28' E.$, 2.87 chs. dist.
	The cor. of secs. 13 and 24, T. 42N., R. 34 E., bears S. $0^{\circ} 28' W.$, 37.16 chs. dist.