

RETRACEMENT OF THE EIGHTH STANDARD PARALLEL NORTH, R. 37 E.

CHAINS

N. 89° 45' W., beginning new measurement.

4.67 The 1/4 sec. cor. of sec. 6, T. 40 N., R. 37 E., hereinafter described.

40.35 The standard cor. of T. 41 N., Rs. 36 and 37 E., monumented with an iron post, 3 ins. diam., set, mkd., and witnessed as described in the official record. This corner is Nevada Planning Department of the Nevada Highway Department station CAIN and its geographic position is latitude 42° 22' 56.025" N. and longitude 117° 52' 02.042" W.

from which

The closing cor. of T. 40 N., Rs. 36 and 37 E., monumented with an iron post, 3 ins. diam., set, mkd., and witnessed as described in the official record, bears N. 89° 47' W., 6.44 chs. dist.

DEPENDENT RESURVEY OF THE N. BDY. OF T. 39 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA.

Re-establishment of the Survey Executed by H. B. Maxson, Deputy Surveyor, in 1888.

Beginning at the cor. of Tps. 39 and 40 N., Rs. 37 and 38 E., an iron post, 3 ins. diam., set in cor. of fence bearing N. 64° 48' E. and N. 89° 48' W., mkd. and witnessed as described in the official record.

S. 89° 54' W., bet. secs. 1 and 36.

Over mountainous land, through medium undergrowth; desc. 270 ft. over NW. slope. Along S. side of a fence.

22.10 Trail road, bears N. and S.; wash, 10 lks. wide, 1 ft. deep, drains N.; asc. 90 ft. over E. slope.

38.20 Spur, slopes NW.

40.08 Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T40N R37E
 1/4 — S 36
 S 1
 T39N

1965

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Desc. 140 ft. over W. slope.