

SURVEY OF THE SUBDIVISION, T. 40 N., R. 37 E.

CHAINS		
	From this corner, a windmill, bears N. 15° 11' E., 26.86 chs. dist.	
79.96	The cor. of secs. 7, 8, 17 and 18. Land, gentle rolling to nearly level. Soil, sandy loam. Undergrowth, shadscale and greasewood.	
	WEST, bet. secs. 7 and 18.	
	Over nearly level land, through medium undergrowth.	
8.00	Trail road, bears NNE. and SSW.	
16.40	Desert road, bears NNE. and SSW.	
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T40N R37E $\frac{1}{4} \frac{S}{S} \frac{7}{18}$ 1965</p>	
	raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.	
82.31	Intersect the E. bdy. of sec. 12, T. 40 N., R. 36 E., in fence bearing N. and S. Point for the closing cor. of secs. 7 and 18. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T40N R36E R37E S 12 $\frac{S}{S} \frac{7}{18}$ CC 1965</p>	
	raise a mound of stone, 2 ft. base, 2 ft. high, E. of cor.	
	from this corner	
	The cor. of secs. 12 and 13, T. 40 N., R. 36 E., an iron post, 2 ins. diam., set in fence bearing N. and S. and mkd. as described in the official record, bears SOUTH, 7.37 chs. dist.	
	The 1/4 sec. cor. of sec. 12, T. 40 N., R. 36 E., an iron post, 1 in. diam., set in fence bearing N. and S. and mkd. as described in the official record, bears NORTH, 32.63 chs. dist.	
	Land, nearly level.	