

## SURVEY OF THE SUBDIVISION, T. 40 N., R. 37 E.

## CHAINS

The point for the W.  $\frac{1}{4}$  sec. cor. of sec. 6, at 40.00 chs. in latitude from the closing cor. of secs. 6 and 7 and on the E. bdy. of sec. 1, T. 40 N., R. 36 E.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T40N  
R36E R37E  
 $\frac{1}{4}$   
S 6

1965

raise a mound of stone, 2 ft. base, 2 ft. high, E. of cor.

from this corner

The  $\frac{1}{4}$  sec. cor. of sec. 1, T. 40 N., R. 36 E., an iron post, 1 in. diam., set in fence bearing N. and S. and mkd. as described in the official record, bears SOUTH, 7.43 chs. dist.

The cor. of sec. 1, for lots 1 and 8, T. 40 N., R. 36 E., an iron post, 1 in. diam., set in fence bearing N. and S. and mkd. as described in the official record, bears NORTH, 32.57 chs. dist.

From the cor. of secs. 5, 6, 7 and 8.

N.  $0^{\circ} 04'$  W., bet. secs. 5 and 6.

Over nearly level land, through medium undergrowth.

36.90 Improved gravel road, bears NE. and SW.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 5 and 6.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T40N R36E  
 $\frac{1}{4}$   
S 6 | S 5

1965

set a stone, 20x14x12 ins., W. of cor.

82.71 Intersect the Eighth Standard Parallel North.

Point for the closing cor. of secs. 5 and 6.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R37E  
S 31  
S 6 | S 5  
T40N  
CC

1965