DEPENDENT RESURVEY OF THE EAST BOUNDARY T. 45 N., R. 51 E.

	T. 45 N., R. 51 E.
CHAINS	Land, rolling. Soil, rocky and sandy loam.
. C.	Undergrowth, native grass and sagebrush.
•	
	N. 0° 01' W., along the E. bdy. of sec. 1.
* · · · · · · · · · · · · · · · · · · ·	Over rolling land, drains W.; through medium undergrowth.
3.38	The closing cor. of secs. 6 and 7, T. 45 N., R. 52 E., hereinafter described.
39.81	The ½ sec. cor. of sec. 1 and 6, monumented with a rhyolite stone, 14x10x4 ins., firmly set and plainly mkd. with ½ on W. face. This corner now refers to the ½ sec. cor. of sec. 1, only.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T45N
	R51E
	1965
\$	raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor. and bury the original cornerstone alongside the iron post.
	N. 0° 14' E., beginning new measurement.
3.57	The ½ sec. cor. of sec. 6, T. 45 N., R. 52 E., herein-after described.
39.93	The NE. cor. of T. 45 N., R. 51 E., monumented with a rhyolite stone, 14x4x7 ins., firmly set in the ground,
	mkd., and witnessed as described in official records. I mark this monument AM.
43.79	Intersect the Ninth Standard Parallel North.
	Point for the closing cor. of sec. 6.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to cap, 3 ft. base, with brass cap mkd.
	T46N R52E S 31
	S 6 T45N R52E CC
	1965