

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 45 N., R. 52 E.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

	T45N	R52E
¼	S	6
	S	7

1965

raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of cor.

82.95 Intersect the E. bdy. of T. 45 N., R. 51 E.

Point for the closing cor. of secs. 6 and 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

	T45N	
R51E		R52E
S 1		S 6CC
		S 7

1965

raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

From this corner the cor. of secs. 1 and 12, T. 45 N., R. 51 E., bears S. 0° 01' E., 3.38 chs. distance.

Land, rolling.
Soil, rocky and sandy.
Undergrowth, native grass and sagebrush.

The point for the W. ¼ sec. cor. of sec. 7 on the E. bdy. of T. 45 N., R. 51 E., at midpoint on the W. bdy. of sec. 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone to cap, 4 ft. base, with brass cap mkd.

	T45N
	R52E
¼	
S	7

1965

from which

The E. ¼ sec. cor. of sec. 12, T. 45 N., R. 51 E., bears S. 0° 03' W., 3.32 chs. distance.

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 04' W., between secs. 5 and 6.

Over rolling land, draining SW., through medium undergrowth.