

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 45 N., R. 52 E.

CHAINS	
24.00	Small wash, course SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T45N R52E $\frac{1}{4}$ S 6 S 5 1965 </div> raise a mound of stone, 2 ft. base, and 2 ft. high, W. of cor.
62.70	Spur, slopes WNW.; descend a gradual N. slope.
80.12	Intersect the Ninth Standard Parallel North. Point for the closing cor. of secs. 5 and 6. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone to cap, 5 ft. base, with brass cap mkd. <div style="text-align: center;"> T45N R52E S 32 <hr style="width: 50%; margin: 0 auto;"/> S 6 S 5 CC T45N 1965 </div> from which <div style="text-align: center;"> The standard $\frac{1}{4}$ sec. cor. of sec. 32, bears N. 89° 55' E., 17.90 chs. distance. </div> Land, rolling. Soil, rocky and sandy. Undergrowth, native grass and sagebrush.
	<hr/> The point for the N. $\frac{1}{4}$ sec. cor. of sec. 5 on the Ninth Standard Parallel North and at midpoint on the N. bdy. of sec. 5. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone to cap, 4 ft. base, with brass cap mkd. <div style="text-align: center;"> T45N R52E <hr style="width: 50%; margin: 0 auto;"/> $\frac{1}{4}$ S 5 T45N 1965 </div> from which <div style="text-align: center;"> The standard cor. of secs. 32 and 33, bears S. 89° 58' E., 15.18 chs. distance. </div> <hr/>