

T. 6 S., R. 57 E.

CHAINS

The following field notes are those of the survey of the boundaries and subdivision of T. 6 S., R. 57 E. The survey was undertaken at the request of the District Manager and State Director to facilitate administration of the area.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated June 11, 1965.

The direction of the lines of this survey were determined by sustained angulation carried forward from lines WHITE SIDES to TUNGSTEN and PAHRANAGAT to WHITE SIDES of the U.S.C. & G.S. triangulation system.

The vertical angles of measurements made on the slope were ascertained by clinometers in good adjustment; the horizontal equivalents only are entered in the field notes.

The geographic position of the southeast corner of T. 6 S., R. 57 E., is $37^{\circ} 22' 32.74''$ N. latitude and $115^{\circ} 31' 08.18''$ W. longitude.

The average magnetic declination was found to be 16° E.

Refer to the field notes of T. 7 S., R. 58 E. for the establishment of the township corners prior to the beginning of the surveys described in these field notes.

SOUTH BOUNDARY OF T. 6 S., R. 57 E.

From the cor. of Tps. 6 and 7 S., Rs. 57 and 58 E., an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of T. 7 S., R. 57 E.

WEST, bet. secs. 1 and 36.

Over level land, through scattered Joshua trees.

28.00 Graveled road, bears N. $67^{\circ} 30'$ E. and S. $67^{\circ} 30'$ W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T6S R57E
 $\frac{1}{4}$ S36
S1
T7S

1965

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

80.00 Point for the cor. of secs. 1, 2, 35 and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.