

DEPENDENT RESURVEY, T. 30 N., R. 34 E.

CHAINS

The following field notes are those of the dependent resurvey of the section line between sections 22 and 27, T. 30 N., R. 34 E.

Line between sections 22 and 27, surveyed by Hatch and Eaton in 1871, and resurveyed by H. B. Maxson in 1895.

The resurvey was requested by the District Manager and State Director to facilitate the administration of the area.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated October 25, 1965.

The direction of the lines of this survey was determined by equal altitude observations on the sun. All measurements were double-chained and the mean distance used. The vertical angles of measurements made on the slope were ascertained by a clinometer in good adjustment; the horizontal equivalents only are entered in the field notes. In order to simplify the record, the true lines notes, only, are supplied herewith, which refer to the completed resurvey.

The geographic position for the northeast corner of section 27 is at latitude 40° 26' 57.08" N. and longitude 118° 07' 59.04" W., as determined from tie to U.S.G.S. Bench Mark, 15 JRH, located in section 19, T. 30 N., R. 35 E.

The magnetic declination was found to be 17° East.

DEPENDENT RESURVEY OF THE SECTION LINE BETWEEN SECTIONS 22 AND 27, T. 30 N., R. 34 E., MDM., NEVADA

Re-establishment of the survey executed by Hatch and Eaton, Deputy Surveyors, in 1871, and resurveyed by H. B. Maxson, Deputy Surveyor, in 1895

The corner of sections 22, 23, 26 and 27, monumented with a stone, 26x12x8 ins., firmly set in a mound of stone and plainly marked with 2 notches on the E. and S. faces.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T30N	R34E
S 22	S 23
S 27	S 26
1965	

bury the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.

from which