

## DEPENDENT RESURVEY OF THE S. BDY. OF T. 17 S., R. 51 E.

CHAINS	
	S. 89° 57' W., bet. secs. 6 and 31. Over rolling land; desc. gentle W. slope.
4.80	Dozed road, bears NW. and SE.
8.00	Wash, 15 lks. wide, 2 ft. deep, drains S.; asc. gentle W. slope.
12.50	Trail road, bears NNW. and SSE.
25.00	Base of ascent, bears N. and S.; asc. 100 ft. over E. slope.
40.07	The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a stone, 12x10x10 ins., mkd. $\frac{1}{4}$ on N. face and firmly set in a mound of stone.  At the corner point  Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to top, 5 ft. base, with brass cap mkd.  <div style="text-align: center;">           T17S R51E  <math>\frac{1}{4}</math> <math>\frac{S}{S}</math> <math>\frac{31}{6}</math>            T18S             1966         </div> bury the original corner stone alongside the iron post.  <hr style="width: 20%; margin: auto;"/> N. 89° 14' W., beginning new measurement.  Asc. 150 ft. over E. slope.
6.50	Spur, slopes N.; desc. 270 ft. over W. slope.
22.50	Wash, 20 lks. wide, 4 ft. deep, drains N.; asc. 110 ft. over E. slope.
33.60	Spur, slopes N.; desc. 170 ft. over W. slope.
38.35	The cor. of Tps. 17 and 18 S., Rs. 50 and 51 E., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.  Land, rolling and mountainous. Soil, shallow sand and rocky. Vegetation, greasewood and creosote.

DEPENDENT RESURVEY OF THE E. BDY. OF T. 17 S., R. 51 E.,  
MDM., NEVADA

Reestablishment of the survey executed by  
E. A. Carter, U.S. Deputy Surveyor, in 1881.

---