

DEPENDENT RESURVEY OF THE E. BDY. OF T. 17 S., R. 51 E.

CHAINS	
4.00	Wash, 30 lks. wide, 3 ft. deep, drains W.
19.40	Wash, 20 lks. wide, 3 ft. deep, drains SW.
35.90	Bladed road, bears E. and W.
40.07	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T17S R51E R52E $\frac{1}{4}$ S 12 S 7 1966</p>
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
80.14	<p>Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T17S R51E R52E S 1 S 6 S 12 S 7 1966</p>
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	<p>Land, level. Soil, sand and gravel. Vegetation, greasewood and creosote.</p>
	NORTH, bet. secs. 1 and 6.
	Over level land, through scattered vegetation.
24.20	Wash, 15 lks. wide, 1 ft. deep, drains WSW.
40.07	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T17S R51E R52E $\frac{1}{4}$ S 1 S 6 1966</p>