

FOURTH STANDARD PARALLEL SOUTH, R. 52 E.

CHAINS	
	<p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>51.40 Graded road, bears N. and S.</p> <p>51.50 Telephone line, bears N. and S.</p> <p>73.67 The closing cor. of secs. 5 and 6, T. 17 S., R. 52 E., hereinafter described.</p> <p>81.88 Point for the standard cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T16S R52E <u>S 31 S 32</u></p> <p style="text-align: center;">T17S</p> <p style="text-align: center;">1966</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Land, level. Soil, sandy clay. Vegetation, creosote and greasewood.</p>
	<p>S. 89° 58' W., along the S. bdy. of sec. 31.</p> <p>Over level land, through scattered vegetation.</p> <p>33.73 The ¼ sec. cor. on the N. bdy. of sec. 6, T. 17 S., R. 52 E., hereinafter described.</p> <p>40.94 Point for the standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T16S R52E <u>¼ S 31</u></p> <p style="text-align: center;">T17S</p> <p style="text-align: center;">1966</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>53.30 Graded road, bears NE. and SW.</p> <p>73.27 The closing cor. of T. 17 S., Rs. 51 and 52 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of T. 17 S., R. 51 E., executed concurrently under this same group.</p>