

## DEPENDENT RESURVEY, T. 17 S., R. 52 E.

## CHAINS

74.38

The closing cor. of secs. 3 and 4, on the Fourth Standard Parallel South, monumented with a stone, 15x10x8 ins., mkd. CC on the S. face, 3 notches on the E. and W. edges and firmly set.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T16S R52E

S 34

S 4 | S 3

CC

T17S

1966

raise a mound of stone, 4 ft. base, 2 ft. high, S. of cor. and bury the original corner stone alongside the iron post.

From this cor., the standard cor. of secs. 33 and 34, T. 16 S., R. 52 E., bears S. 89° 28' W., 8.73 chs. dist.

Land, level.

Soil, sandy clay and gravel.

Vegetation, greasewood and creosote brush.

The point for the N. ¼ sec. cor. of sec. 3, on the Fourth Standard Parallel South and at midpoint on the N. bdy. of sec. 3.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T16S R52E

¼ S 3

T17S R52E

1966

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor. the standard ¼ sec. cor. of sec. 34, T. 16 S., R. 52 E., bears S. 89° 28' W., 8.655 chs. dist.

From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp.

N. 3° 25' W., bet. secs. 32 and 33.

Over rolling land, through scattered vegetation; desc. 50 ft. over gentle NW. slope.