

DEPENDENT RESURVEY OF A PORTION OF
THE S. BDY. T. 14 N., R. 66 E.

CHAINS

39.93

The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, monumented with a squared wooden post, 28 ins. long, $1\frac{1}{2}$ ins. square, plainly mkd. and loosely set in a mound of earth.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T14N R66E

$\frac{1}{4}$ S 33
S 4

T13N R66E

1966

bury the original wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

N. $89^{\circ} 28' W.$, beginning new measurement.

Over level land.

5.20

Fence, bears NE. and SW.

14.10

Oil surfaced road, bears NE. and S., connecting U.S. Highway Nos. 6 and 50, which is 2.00 chs. N., with U.S. Highway No. 93.

17.50

U.S. Highway Nos. 6 and 50, bears N. $66\frac{1}{2}^{\circ} E.$ and S. $66\frac{1}{2}^{\circ} W.$

25.10

Fence, bears ENE. and WSW.

39.93

The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the N. bdy. of T. 13 N., R. 66 E., executed under Group No. 444.

From this cor., U.S.C.&G.S. triangulation station ELY WEST BASE, monumented with a brass tablet, 3 ins. diam., firmly set in a concrete block, 10x10x6 ins. above ground, bears S. $19^{\circ} 46' 28'' W.$, 13.627 chs. dist.

Land, level.

Soil, sandy clay.

Undergrowth, sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE N. BDY.
T. 14 N., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the survey executed by
E. B. Monroe and A. G. Bateman, U.S. Deputy Surveyors,
in 1871.

From the cor. of Tps. 14 and 15 N., Rs. 66 and 67 E.

N. $89^{\circ} 52' W.$, bet. secs. 1 and 36.