

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH,
THROUGH RANGE 67 EAST

CHAINS	
	<p>Reestablishment of the survey executed by E. B. Monroe and A. G. Bateman, U. S. Deputy Surveyors, in 1871</p> <hr/> <p>Beginning at the standard corner of Tps. 11 N., Rs. 67 and 68 E., monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.</p> <p>N. 89° 51' W., along the S. bdy. of sec. 36.</p> <p>Over nearly level land, through medium heavy under- growth.</p> <p>40.34 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 36, at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div>SC T11N R67E <u>½ S 36</u></div> <p>1967</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>80.68 The standard cor. of secs. 35 and 36, monumented with the remains of a squared post, 1½x1½x36 ins., loosely set in a mound of earth, with some scribe marks visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div>SC T11N R67E <u>S 35 S 36</u></div> <p>1967</p> <p>bury the squared post alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Land, nearly level. Soil, sandy clay loam. Undergrowth, sagebrush, rabbitbrush and greasewood.</p> <hr/> <p>N. 89° 52' W., along the S. bdy. of sec. 35.</p> <p>Over nearly level land, through medium heavy under- growth.</p>