

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH,
THROUGH RANGE 67 EAST

CHAINS	SC	
	T11N	R67E
	<u>1/4 S</u>	<u>32</u>
	1967	
	bury the squared post alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.	
	S. 89° 54' W., beginning new measurement.	
	Over nearly level land, through medium heavy undergrowth.	
17.10	Trail road, bears NE, and SW.	
40.19	The standard cor. of secs. 31 and 32, monumented with the remains of a squared post, 2x2x24 ins., loosely set in the ground, with scribe marks dimly visible.	
	At the corner point	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.	
	SC	
	T11N	R67E
	<u>S 31</u>	<u>S 32</u>
	1967	
	bury the squared post alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.	
	Land, nearly level.	
	Soil, sandy and gravelly clay loam.	
	Undergrowth, sagebrush, rabbitbrush and greasewood.	
	N. 89° 29' W., along the S. bdy. of sec. 31.	
	Over nearly level land, through medium heavy undergrowth.	
6.70	Road, improved, bears ENE. and WSW.	
40.09	The standard 1/4 sec. cor. of sec. 31, monumented with the remains of a squared post, badly decayed, dimly mkd. and loosely set in a mound of earth.	
	At the corner point	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.	