DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES T. 12 N., R. 67 E.

	T. 12 N., R. 67 E.
CHAINS	
•	T12N R67E
	$\mathbf{S} \cdot 3 \mid \mathbf{S} \cdot 2 \mathbf{S} \cdot $
	1967
	reset the squared wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
/ /	This corner is 1.40 chs. West of a trail road, bears N. and S.
	N. 1° 59' E., beginning new measurement.
	Over nearly level land, through scattered undergrowth, along a trail road, bearing N. and S.
39.38	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent dependent resurvey of the South Boundary of T. 13 N., R. 67 E., executed under this same Group.
	Land, nearly level. Soil, sandy and gravelly clay loam. Undergrowth, sagebrush and greasewood.
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent dependent resurvey of the North Boundary of T. 11 N., R. 67 E., executed under this same Group.
	N. 0° 22' W., bet secs. 33 and 34.
	Over nearly level land, through scattered undergrowth.
3.80	Trail road, bears E. and W.
20.00	Road, bladed, bears NNE. and SSW.
28.40	Trail road, bears NE. and SW.
39.68	Point for the ½ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.