DEPENDENT RESURVEY OF THE SOUTH BOUNDARY T. 13 N., R. 67 E.

	1. 13 N ₀ , R ₀ 0/ E ₀
~ CHAINS	Beginning at the corner of Tps. 12 and 13 N., Rs. 67 and 68 E., monumented with the remains of a squared wooden
\tau_1	post, 2 ins. square, 24 ins. long, with scribe marks dimly visible and loosely set in a mound of stone.
:75	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T13N
* "	R67E R68E S 36 S 31 S 1 S 6
~	Tĺ2N , ~
* * * * * * * * * * * * * * * * * * * *	1967 (n. 1967) (
	reset the squared post alongside the iron post and raise a mound of stone, 4 ft. base, 2 ft. high, S. of cor.
1701	From this corner, a copper-coated steel stake, ½ in. diam, firmly driven in the ground, marked U-64-1 1962, established in connection with the tellurometer survey
	under Group No. 389, bears N. 13° 11' W., 4.67 chs. dist.
	N. 89° 53' W., bet. secs. 1 and 36.
	Over rolling land, through medium heavy undergrowth; desc. 210 ft. over a gradual W. slope.
40.10	Point for the 2 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam, 4 ins. in the ground to solid rock and in a mound of stone to top, 4 ft. base, with brass cap mkd.
	T13N - R67E
	T12N
	1966 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
40.20	Wash, 10 1ks. wide, 2 ft. deep, drains WSW.; desc. 160 ft. over a gradual W. slope to the sec cor.
68,00	Wash, 10 1ks. wide, 2 ft. deep, drains WSW.
74.90	Wash, 5 1ks. wide, 1 ft. deep, drains WSW.