DEPENDENT RESURVEY OF THE SOUTH BOUNDARY T. 13 N., R. 67 E.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

1966

reset the squared wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

N. 89° 47' W., beginning new measurement.

Over nearly level land, along south edge of a plowed field and along a fence.

40.39

The cor. of secs. 5, 6, 31 and 32 in fence bearing E. and W., monumented with the remains of a squared wooden post, 2 ins. square, 24 ins. long, with scribe marks T XIII N R LXVII E S XXXI S VI clearly visible and firmly set in the ground alongside a fence post.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

1966

reset the squared wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

From this corner, the northeast corner of a pumphouse of a well, bears N. 13° 21' W., 20.56 chs. dist.

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, none.

Undergrowth, sagebrush and greasewood.

N. 89° 54' W., bet. secs. 6 and 31.

Over nearly level land, along the south edge of a plowed field and along the north side of a fence.