

DEPENDENT RESURVEY, MT. DIABLO BASE LINE, THROUGH R. 53 E.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

SC
TIN R53E
½ S 32

1966

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

From this corner, the SW. cor. of the main building at Mount Diablo State Highway maintenance yard, bears N. 6° 39' W., 33.28 chs. dist.

82.06 Point for the standard cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

SC
TIN R53E
S 31 | S 32

1966

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Land, nearly level.
Soil, sandy gravel.
Undergrowth, shadscale and budsage.

N. 89° 55' W., along the S. bdy. of sec. 31.

Over nearly level land, through medium undergrowth.

35.65 Well and pump, bears NORTH, 2.84 chs. dist.

41.03 Point for the standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

SC
TIN R53E
¼ S 31

1966