		DEPENDENT RESURVEY, WEST BOUNDARY, T. 1 N., R. 53 E.
	CHAINS 33.31	Point for the ½ sec. cor. of sec. 12, T. 1 N., R. 52 E., at 40.00 chs. in latitude from the cor. of secs. 12 and 13, T. 1 N., R. 52 E.
		Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	*	T1N R52E R53E 戈
	•	S 12
		1966
		raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	40.62	The 表 sec. cor. of sec. 7, T. 1 N., R. 53 E., monumented with a lava stone, 10x10x12 ins., firmly set and plainly mkd. 表 on the E. face.
		At the corner point
		Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
		T1N R52E R53E 表 S 7
	,	1966
		bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.
N. 0° 01' E., beginning new meas		N. 0° 01' E., beginning new measurement.
	•	Over nearly level land.
	5.90	Wash, 20 1ks. wide, 2 ft. deep, drains SE.
	32.40	Gravel road, bears SSE. and NNW.
	32.69	Point for the cor. of secs. 1 and 12, T. 1 N., R. 52 E., at 80.00 chs. in latitude from the cor. of secs. 12 and 13, T. 1 N., R. 52 E.

T1N					
R.	52E	R5	3E		
S	1	٠,	-		
S	12	S	/		

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

1966