

DEPENDENT RESURVEY, WEST BOUNDARY, T. 1 N., R. 53 E.

CHAINS

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

40.66

The cor. of secs. 6 and 7, T. 1 N., R. 53 E., monumented with a lava stone, 6x8x10 ins., firmly set alongside a steel fence post and plainly mkd. with 5 notches on the S. face and 1 notch on the N. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1N	
R52E	R53E
S 1	S 6
	S 7

1966

bury the original corner stone and reset the steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

Land, nearly level.

Soil, sandy gravel.

Undergrowth, shadscale and budsage.

N. 2° 21' E., along the W. bdy. of sec. 6.

Over nearly level land, through medium undergrowth.

3.42

The cor. of Tps. 1 and 2 N., R. 52 E., monumented with a lava stone, 6x8x10 ins., firmly set and plainly mkd. CC 52E on W. face, 1 N. on S. face, 2 N. on N. face and with 6 notches on the N., S. and W. faces.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T2N	T1N
R52E	R53E
S 36	S 6
S 1	
T1N	

1966

bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

32.00

Trail road, bears E. and W.

34.10

State Highway 25, curving SSE. and NNW.

37.77

Point for the ¼ sec. cor. of sec. 6, T. 1 N., R. 53 E., at proportionate distance; there is no remaining evidence of the original corner.