

FIFTH STANDARD PARALLEL NORTH, THROUGH R. 64 E.

CHAINS

Beginning at the standard corner of T. 26 N., Rs. 64 and 65 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of T. 26 N., R. 65 E.

N. $89^{\circ} 59'$ W., along the S. bdy. of sec. 36.

Over nearly level dry lake bed, through dense undergrowth.

1.19

The closing cor. of secs. 1 and 2, monumented with a limestone, $14 \times 10 \times 6$ ins., firmly set and plainly mkd. 1 notch on the E. edge, 5 notches on the W. edge and CC on the S. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T26N R64E

S 36

S 2 | S 1

T25N R64E

CC

1966

bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

39.99

The standard $\frac{1}{4}$ sec. cor. of sec. 36, monumented with a limestone, $16 \times 12 \times 8$ ins., firmly set and plainly mkd. SC $\frac{1}{4}$ on the N. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

SC

T26N R64E

$\frac{1}{4}$ S 36

1966

bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

S. $89^{\circ} 57'$ W., beginning new measurement.

Over nearly level land, through dense undergrowth.

39.98

The standard cor. of secs. 35 and 36, monumented with a limestone, $14 \times 8 \times 8$ ins., firmly set and plainly mkd. 1 notch on the E. edge, 5 notches on the W. edge and SC on the N. face.

At the corner point