

FIFTH STANDARD PARALLEL NORTH, THROUGH R. 64 E.

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone to cap, with brass cap mkd.</p> <p style="text-align: center;">SC T26N R64E <u>¼ S 32</u></p> <p style="text-align: center;">1966</p> <p>bury the original corner stone alongside the iron post.</p> <hr/> <p>S. 89° 51' W., beginning new measurement.</p> <p>Ascend 250 ft. over an ENE. slope.</p> <p>0.20 Head of ravine, drains N.</p> <p>16.90 Spur, slopes E.; continue ascent 40 ft. along steep S. slope.</p> <p>40.01 The standard cor. of secs. 31 and 32, monumented with a limestone, 18x12x5 ins., firmly set and plainly mkd. 5 notches on the E. edge, 1 notch on the W. edge and SC on the N. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to cap, 5 ft. base, with brass cap mkd.</p> <p style="text-align: center;">SC T26N R64E <u>S 31 S 32</u></p> <p style="text-align: center;">1966</p> <p>bury the original corner stone alongside the iron post.</p> <p>Land, rolling mountainous. Soil, sandy clay, light gravel and rocky. Undergrowth, sagebrush and native grasses. Timber, juniper, cedar and pinon pine.</p>
0.72	<p>S. 89° 55' W., along the S. bdy. of sec. 31.</p> <p>Over rolling mountainous land, through dense timber; descend 310 ft. along SSW. slope.</p> <p>The closing corner of T. 25 N., Rs. 63 and 64 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.</p> <p>The geographic position of this corner is latitude 40° 04' 37.390" N. and longitude 114° 47' 16.970" W., as determined by the tellurometer survey for the protraction survey, under Group No. 389, Nevada.</p>