

DEPENDENT RESURVEY OF A
PORTION OF THE FIFTH STANDARD PARALLEL NORTH,
THROUGH RANGE 65 EAST

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T26N R65E <u>¼ S 31</u></p> <p style="text-align: center;">1966</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
60.00	Enter Goshute Lake bed (dry), edge bears NNW. and SSE.
79.92	<p>The standard cor. of T. 26 N., Rs. 64 and 65 E., monumented with a limestone, 12x10x4 ins., mkd. SC and 6 notches on the N. face, 6 notches on the W. face and 6 notches on the E. face and firmly set in a mound of earth. This appears to be the 1909 remonumentation.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T26N R64E R65E <u>S 36 S 31</u></p> <p style="text-align: center;">1966</p> <p>bury the marked stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Land, nearly level. Soil, sandy clay loam. Undergrowth, sagebrush and greasewood.</p>
<p>DEPENDENT RESURVEY OF THE E. BDY. OF T. 26 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>Reestablishment of the survey executed by Preble and Thorburn, U. S. Deputy Surveyors, in 1881.</p>	
	<p>From the standard cor. of T. 26 N., Rs. 65 and 66 E., monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of the Fifth Standard Parallel North, through Range 66 East.</p> <p>N. 0° 02' E., bet. secs. 31 and 36.</p> <p>Over nearly level land, through medium undergrowth.</p>
3.20	Trail road, bears NE. and SW.
19.00	Abandoned highway, bears NE. and SW.
21.70	Telephone line parallels abandoned highway.
40.865	Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.