

## DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 26 N., R. 65 E.

CHAINS

T26N  
R65E R66E

$\frac{1}{2}$   
S 1 | S 6

1966

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

80.52 The cor. of Tps. 26 and 27 N., Rs. 65 and 66 E., monumented with a birch post, 2 ins. square, 12 ins. long, with illegible scribe marks, in a mound of earth and stone.

This corner was shown to me by Peter Cordiano, a resident in the vicinity for 50 years or more; it is locally accepted as the original corner.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T27N  
R65E R66E

S 36 | S 31  
S 1 | S 6

T26N

1966

reset the wooden corner post alongside the iron post and raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, S. of cor.

Land, nearly level.  
Soil, sandy clay.  
Undergrowth, sagebrush.

DEPENDENT RESURVEY OF THE W. BDY. OF T. 26 N., R. 65 E.,  
MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the survey executed by  
Preble and Thorburn, U. S. Deputy Surveyors,  
in 1881.

From the standard cor. of T. 26 N., Rs. 64 and 65 E.

N.  $0^{\circ} 13'$  W., bet. secs. 31 and 36.

Over level dry Goshute Lake bed.

40.31 Point for the  $\frac{1}{2}$  sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.