INDEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH, THROUGH RANGE 36 EAST

THROUGH RANGE 36 EAST		
	CHAINS	
		SC T16N R36E
	,	½ S 32
		1966
	,	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
		Desc. 20 ft. over a continued SW. slope.
	41.50	Shallow ravine, drains S.; desc. 100 ft. along a broken S. slope.
	54.80	Shallow ravine, drains SSW.; desc. 40 ft. over a rolling S. slope.
	61.90	Wash, 40 lks. wide, 3 ft. deep, drains NW.; asc. 20 ft. over a NE. slope.
	64.40	Low spur, slopes WNW. from SE.; desc. 40 ft. over a WSW. slope.
	77.90	Wash, 20 lks. wide, 2 ft. deep, drains NW. for about 2.50 chs. to junction with wash from ESE.; asc. 20 ft. over a NE. slope.
	79.40	Low white spur, solid rock, slopes NW.; desc. 10 ft. over a SW. slope.
	80.00	Point for the standard cor. of secs. 31 and 32.
	,	Set an iron post, 28 ins. long, 2 ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to cap, with brass cap mkd.
	,	SC T16N R36E
	,	S 31 S 32
	-	. 1966
		Land, mountainous. Soil, sandy loam and rocky. Timber, several scattered pinon. Undergrowth, sagebrush and native grasses.
		WEST, along the S. bdy. of sec. 31.
		Over mountainous land, through medium undergrowth; desc. 30 ft. over rolling land draining N.
	11.60	Wash, 10 lks. wide, 2 ft. deep, drains N.; asc. 80 ft. over a NE. slope.
	20.00	Top ascent, on N. slope; desc. 50 ft. over a WNW. slope.
	23.40	Ravine, drains NNE.; asc. 50 ft. over an E. slope.
	I	