

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 N., R. 36 E.

CHAINS	
23.10	Spur, slopes E.; ascend 70 ft. over a rolling SE. slope.
30.00	Flat-topped ridge, bears NE. and SW.; continue along top of ridge.
34.00	Leave top of ridge, bears NW. and SE.; descend 20 ft. along a rolling E. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T18N R36E $\frac{1}{4}$ S 2 S 1 1966 </div> from which A pinon, 4 ins. diam., bears N. $38\frac{1}{2}^{\circ}$ E., 40 lks. dist., mkd. X BT. A juniper, 5 ins. diam., bears S. $11\frac{1}{4}^{\circ}$ W., 24 lks. dist., mkd. $\frac{1}{4}$ S2 BT. Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Descend 30 ft. along a rolling E. slope.
52.80	Ravine, drains SE.; ascend 360 ft. over a S. slope.
65.00	Crest of ridge, bears NNW. and SSE.; ascend 70 ft. along a rolling E. slope.
78.80	Spur, slopes E.; descend 10 ft. over a N. slope.
79.81	Intersect the S. bdy. of sec. 36, T. 19 N., R. 36 E. Point for the closing cor. of secs. 1 and 2. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., over a cross (X) marked on solid bedrock, and in a mound of stone to cap, 4 ft. base, with brass cap mkd. <div style="text-align: center;"> T19N R36E S 36 S 2 S 1 T18N CC 1966 </div> from which A pinon, 12 ins. diam., bears S. $56\frac{1}{2}^{\circ}$ E., 38 lks. dist., mkd. T18N R36E S1 CC BT.