

INDEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH,
RANGE 37 EAST

CHAINS	
42.00	Wash, 40 lks. wide, 3 ft. deep, drains NW.
44.00	Bladed dirt road, bears SSE. and NNW.; asc. 80 ft. over an E. slope.
51.20	Spur, slopes NE.; desc. 30 ft. over a NW. slope.
55.40	Ravine, drains NE.; asc. 160 ft. over an E. slope.
72.00	Slope changes, asc. 20 ft. over a rolling NNE. slope.
80.00	Point for the standard cor. of secs. 31 and 32.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	SC T16N R37E <u>S 31 S 32</u>
	1966 raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor. Land, mountainous. Soil, sandy clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.
	WEST, along the S. bdy. of sec. 31.
	Over mountainous land, through scattered timber; asc. 10 ft. over a NNE. slope.
1.90	Ridge, bears SE. and WNW.; over a S. slope.
9.50	Low spur, slopes S.; desc. 70 ft. over a W. slope.
19.50	Swale, drains NE.; asc. 60 ft. over a rolling NNE. slope, changing to NE.
35.50	Shallow ravine, drains NE.; asc. 40 ft. over an E. slope.
40.00	Point for the standard ¼ sec. cor. of sec. 31.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	SC T16N R37E <u>¼ S 31</u>
	1966 raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.