

SURVEY OF THE NORTH BOUNDARY OF T. 16 N., R. 37 E.

CHAINS	
	Asc. 280 ft. over a continued steep E. slope.
86.93	The cor. of Tps. 16 and 17 N., Rs. 36 and 37 E., monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.
	Land, gently rolling to mountainous. Soil, sandy clay to sandy clay and rocky. Timber, none. Undergrowth, sagebrush, rabbitbrush and greasewood.
	SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF T. 16 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp.
	N. 0° 01' W., bet. secs. 34 and 35.
	Over mountainous land, through scattered timber; asc. over a gentle WSW. slope.
0.80	Trail road, bears ESE. and WNW.; asc. 140 ft. over a SSW. slope.
11.20	Low ridge, bears ESE. and WNW.; desc. 50 ft. over a NNE. slope.
12.90	Ravine, drains WNW., then SW.; asc. 70 ft. over a broken SSW. slope.
20.60	Bladed dirt road, on curve, bears ESE. and WSW.; over a gentle W. slope.
22.00	Rim, bears E. and W.; desc. 210 ft. over a steep N. slope.
30.40	Ravine, drains W.; asc. 120 ft. over a bare broken S. slope.
39.00	Crest of a rough eroded ridge, bears E. and W.; desc. 10 ft. over a broken NW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, falls on a very steep clay bank and is not practicable to monument at true point.
	Continue over a steep broken NW. slope.
41.52	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 34 and 35.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground and in a collar of stone, with brass cap mkd.
	WC T16N R37E $\frac{1}{4}$ S 34 ↓ S 35 1966