

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
OF T. 16 N., R. 37 E.

CHAINS	
13.80	Shallow ravine, drains NE.; asc. 100 ft. over a rolling S. slope.
21.00	Low spur, slopes S.; desc. 10 ft. over a SW. slope.
23.30	Shallow ravine, drains SE.; asc. 110 ft. over a SE. slope, gradually changing to a rolling S. slope.
33.00	Top of ascent on S. slope; desc. 40 ft. over a rolling SSW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 6 ft. base to cap, with brass cap mkd. <div style="text-align: center;"> T16N R37E $\frac{1}{4}$ $\frac{S 19}{S 30}$ </div> 1966 Desc. 170 ft. over a continued SSW. slope, gradually changing to SW.
52.80	Small wash, drains NNW.; over a gently rolling N. slope.
57.30	Wash, 20 lks. wide, 2 ft. deep, drains N.; asc. 40 ft. over gently rolling land, draining NNE.
77.70	Small wash, drains NNE.; asc. 10 ft. over a gentle E. slope.
80.00	Point for the $80 \frac{1}{16}$ sec. cor. of secs. 19 and 30. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T16N R37E $\frac{1}{16}$ $\frac{S 19}{S 30}$ 80 </div> 1966 raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor. Asc. 40 ft. over an E. slope.
87.36	Intersect the E. bdy. of T. 16 N., R. 36 E. Point for the closing corner of secs. 19 and 30. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T16N R36E R37E S 24 $\frac{S 19}{S 30}$ CC </div> 1966