

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
OF T. 16 N., R. 37 E.

CHAINS

T16N R37E
 $\frac{1}{4}$ $\frac{S 18}{S 19}$

1966

Asc. 30 ft. over a continued S. slope.

44.20 Top of ascent on S. slope; from which the summit of a hill bears N., 1.40 chs. dist. Desc. 120 ft. over a rolling S. slope gradually changing to SW.

73.70 Track road, bears N. and S.; over gently rolling land, draining NNE.

76.50 Small wash, drains NNE.; asc. 10 ft. over an E. slope.

79.00 Trail road, bears NE. and SW.

80.00 Point for the 80 1/16 sec. cor. of secs. 18 and 19.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T16N R37E
 $\frac{1}{16}$ $\frac{S 18}{S 19}$ 80

1966

raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of cor.

80.90 Wash, 10 lks. wide, 3 ft. deep, drains NE.; asc. 30 ft. over a gentle E. slope.

87.21 Intersect the E. bdy. of T. 16 N., R. 36 E.

Point for the closing cor. of secs. 18 and 19.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T16N
R36E | R37E
S 13 | $\frac{S 18}{S 19}$ CC

1966

raise a mound of stone, 3½ ft. base, 2½ ft. high, E. of cor.

from this corner

The cor. of secs. 13 and 24, T. 16 N., R. 36 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of T. 16 N., R. 36 E., surveyed concurrently, bears SOUTH, 11.69 chs. dist.